

Networking: How to configure uplink in private subnet? OR how to resolve external names?

Steps

1. Edit `/etc/network/interfaces` file

This file describes the network interfaces available on your system and how to activate them.

2. It will look like this

```
# The loopback network interface
```

```
auto lo
```

```
iface lo inet loopback
```

```
# The primary internal network interface
```

```
auto eth0
```

```
iface eth0 inet static
```

```
address a.b.c.d           (a,b,c,d is the IP address of internal network)
```

```
netmask e.f.g.h         (e,f,g,h is the netmask address)
```

ADD FOLLOWING LINES IN THE FILE

```
auto eth1
```

```
iface eth1 inet static
```

```
address a.b.c.d           (a,b,c,d is the IP address of external network)
```

```
netmask e.f.g.h         (e,f,g,h is the netmask address)
```

```
gateway v.x.y.z         (v,x,y,z is the IP address of the gateway)
```

3. Edit `/etc/dnsmasq.conf`

Find the line

```
#resolv-file=
```

and change it to

```
resolv-file=/etc/dnsmasq-upstream-resolv.conf
```

where `/etc/dnsmasq-upstream-resolv.conf` contains the upstream name server entry.

Open the file `/etc/dnsmasq-upstream-resolv.conf` and put the following line in it:

```
nameserver <upstream name server ip>
```

where `<upstream name server ip>` is the IP of upstream name server

4. To access external network from virtual machine running in this private subnet, it requires nat rules in IP table.

Those rules can be added using preinstaller script called "install_nat.sh".

On running this script, it will list the available network interfaces and it will ask you to insert external network interface. Once the input is provided, it will add required rules in the IP table.

Networking: How to configure uplink in private subnet? OR how to resolve external names?

Unique solution ID: #1082

Author: Coriolis Technologies

Last update: 2012-06-12 09:59