Screen Display: How to install qxl driver in OpenSuse 12.1

To install the qxl driver on OpenSuse 12.1, follow these steps-

1. Make sure you have these packages installed on system.
   If not, open Start menu | search for Yast | select Yast |
   <enter password when prompted>
   Select **Software Management**
2. Search for the following packages and mark them to install.
   gcc
   xorg-x11-server-sdk
3. Download spice-protocol latest stable package from http://spicespace.org/download.html
4. Open Terminal/Konsole and change to the downloads directory.
5. Become root using command
   su
   <enter password>
6. Extract archieve using command
   tar -xvf spice-protocol-package-name
7. Change to extracted directory -
   cd spice-protocol-source-directory
8. Enter these commands one after other-
   ./configure
   make
   make install
9. Download latest qxl driver from http://xorg.freedesktop.org/archive/individual/driver/
   Check for filename like **xf86-video-qxl-X.X.X.tar.bz2**
10. Extract the archieve using command
    tar -xvf xf86-video-qxl-X.X.X.tar.bz2
11. Change to the extracted directory
    cd xf86-video-qxl-X.X.X
12. Enter these commands one by one
    ./configure
    make
    make install
13. now shutdown your OpenSuse machine to configure it to use Spice.
14. Follow the tutorial to enable the spice client for your machine.

Unique solution ID: #1067
Author: Coriolis Technologies
Last update: 2012-03-07 14:36

(c) 2024 Coriolis Technologies Private Limited <administrator@coriolis.co.in> | 2024-03-29 15:57
URL: http://support.colama.net/faqs/index.php?action=artikel&cat=6&id=68&artlang=en